

ZETA 2.3" Recessed

Spec-grade | Architectural LED Linear Lighting





The Zeta 2.3" recessed mount linear lighting system is available in 2.3" widths and lengths of 2ft, 3ft, and 4ft, delivering simple, powerful illumination for any environment. Its streamlined linear form factor is designed for maximum versatility. With superior flexibility—featuring adjustable wattage and CCT—Zeta products achieve a balanced blend of aesthetics, visual comfort, and lighting performance, making them ideal for the most demanding lighting challenges. This architectural recessed lighting solution is compatible with most 15/16" and 9/16" T-grid ceilings as well as dry ceilings. It is widely used in office spaces, major retail stores, education, government, healthcare, and hospitality settings.

Feature

- Trimless design or flange trim options
- Application flexibility, T-grid or dry ceiling compatible
- Continuous runs or custom pattern
- Available in diffuser, micro reflector, louver and regressed lens
- Available in 2ft, 3ft and 4ft, up to 1000lm/ft, 90+CRI
- Wattage selectable (50%/75%/100%)
- CCT adjustable from 3000K, 3500K, 4000K

PERFORMANCE

Lens	Length	Wattage Selectable	100%DOWN		CCT Adjustable
			Efficacy	Lumen Output	
Diffuser	2'	20W/15W/10W	1050lm/ft	Up to 2100LM	3000K/3500K/4000K
	3'	30W/23W/15W		Up to 3150LM	
	4'	40W/30W/20W		Up to 4200LM	
	8'	80W/60W/40W		Up to 8400LM	
Regressed Lens	2'	20W/15W/10W	900lm/ft	Up to 1800LM	3000K/3500K/4000K
	3'	30W/23W/15W		Up to 2700LM	
	4'	40W/30W/20W		Up to 3600LM	
	8'	80W/60W/40W		Up to 7200LM	
Louver	2'	20W/15W/10W	650lm/ft	Up to 1300LM	3000K/3500K/4000K
	3'	30W/23W/15W		Up to 1950LM	
	4'	40W/30W/20W		Up to 2600LM	
	8'	80W/60W/40W		Up to 5200LM	
Micro Reflector	2'	20W/15W/10W	900lm/ft	Up to 1800LM	3000K/3500K/4000K
	3'	30W/23W/15W		Up to 2700LM	
	4'	40W/30W/20W		Up to 3600LM	
	8'	80W/60W/40W		Up to 7200LM	



Remark:
Lumens are subject to maximum wattage, 4000K with white finish only.

Lumen output may vary $\pm$ 5% base on different CCT and wattage. Actual wattage may vary $\pm$ 5%.

ZETA 2.3" Recessed

Spec-grade | Architectural LED Linear Lighting

PRODUCT ORDERING GUIDE

Example: ZE4B-WH-40W-D10-90TW-D-DFRT

Default Settings: Maximum wattage, 4000K and 100% down.

ZE					90	TW	D		
Product Series	Length	Finish	Wattage	0-10V Dim	CRI	CCT	Lighting Distribution	Down Lens	Mounting
ZE ZETA Linear	2B QuickShip 2 Feet Bold	WH QuickShip White	20W QuickShip 20W/15W/10W Selectable for 2ft	D10 QuickShip 110-277V AC Dims to 10% <i>Tested Dimmers: Lutron® Diva-Dvtv, Leviton® IP-710-DL.</i>	90 QuickShip 90+ CRI	TW QuickShip CCT adjustable 3000K/3500K/ 4000K	D QuickShip 100% downlight	DF QuickShip Diffuser	RT QuickShip Trim
	3B QuickShip 3 Feet Bold	BL QuickShip Black (Only for Continuous Run)	30W QuickShip 30W/23W/15W Selectable for 3ft					LV QuickShip Louwer	RT1: Mount by flanged trim and bracket in Dry ceiling.
	4B QuickShip 4 Feet Bold	CM Make to Order Custom *	40W QuickShip 40W/30W/20W Selectable for 4ft	D01 QuickShip 110-277V AC Dim to 1%				MR Make to Order Micro Reflector*	RT2: Mount by flanged trim and pendant stem in Dry ceiling.
	8B Make to Order 8 Feet Bold* (4ft+4ft for QuickShip)		80W Make to Order 80W/60W/40W Selectable for 8ft*					RL QuickShip Regressed Lens (White Shade)	RT3: Mount by flanged trim to lay on T-grid ceiling / Drop ceiling.
								WW QuickShip Wall Wash Diffuser (30° Tilt)	RS QuickShip Trimless Mount by trimless flanged kit and need plastering in Dry ceiling.
									RH QuickShip Trimless Mount by T-grid hooks to secure in T-grid ceiling / Drop ceiling.

*Make to Order means additional cost and/or lead time on customized fixtures may apply. Some fixtures require an MOQ. Please contact your sales rep for more information.

Damp rated for ambient operating temperature of -20°C to +40°C (-4° to 104°F)


OPTIONAL ACCESSORY

Optional Joiners	Emergency	Optional Sensor (See Page 5 For More)	Optional Pre-assembled Configuration (Diffuser Only)
SJ QuickShip Straight Line Joiner (Optional 40' rolling lens)	EMI Built-in Emergency (Only for diffuser, 4ft length.)	OCC-DDM 100% Down, Dimming Only OCC-DDM-A01 QuickShip OCC-DDM-A02 QuickShip OCC-DDM-A03 QuickShip OCC-DDM-A04 QuickShip OCC-DDM-K01 QuickShip OCC-DDM-K02 QuickShip	1T Make to Order 1FT+Telescoping Section  Adjust from 13"~25"
LJ QuickShip "L" Lit Corner Joiner White L Lit Joiner Only for QuickShip	EMI-8W QuickShip	OCC-DDT 100% Down, Dimming and Tunable White OCC-DDT-A01* Make to Order OCC-DDT-A02* Make to Order OCC-DDT-A03* Make to Order OCC-DDT-A04* Make to Order OCC-DDT-K01* Make to Order	2T QuickShip 2FT+Telescoping Section  Adjust from 24 1/2"~ 36 1/2"
WJ QuickShip Ceiling to Wall Joiner 	EME External Emergency (Field-installed, works for all options) EME-16W QuickShip EME-25W QuickShip		3T QuickShip 3FT+Telescoping Section  Adjust from 36 1/2"~ 48 1/2"

CUSTOM LINE OR SHAPE ORDERING GUIDE

Example: ZEB-R-C18-WH-DF-D10-RT

SHAPE/LENGTH* (CHOOSE 1 & ENTER LENGTH IN FEET)	Finish	Down Lens	0-10V Dim	Mounting
ZEB-R-C Continuous Run Section QuickShip (Enter length in product code above, ex. C18)	WH QuickShip White	DF QuickShip Diffuser	D10 QuickShip 110-277V AC Dims to 10% <i>Tested Dimmers: Lutron® Diva-Dvtv, Leviton® IP-710-DL.</i>	RT QuickShip Trim
ZEB-R-S Lit Square Configuration (Enter length A, ex: S18) QuickShip	BL QuickShip Black (Only for Continuous Run)	LV QuickShip Louwer		RT1: Mount by flanged trim and bracket in Dry ceiling.
ZEB-R-R Lit Rectangular Configuration QuickShip (Enter side lengths A and B, ex. R12/24)	CM Make to Order Custom *	MR Make to Order Micro Reflector*	D01 QuickShip 110-277V AC Dim to 1%*	RT2: Mount by flanged trim and pendant stem in Dry ceiling.
ZEB-R-L Lit L-Shaped Configuration QuickShip (Enter side lengths A and B, ex. L12/24)		RL QuickShip Regressed Lens (White Shade)		RT3: Mount by flanged trim to lay on T-grid ceiling / Drop ceiling.
ZEB-R-T Lit T-Shaped Configuration Make to Order (Enter side lengths A, B and C ex. T04/06/08)*		WW QuickShip Wall Wash Diffuser (30° Tilt)		RS QuickShip Trimless Mount by trimless flanged kit and need plastering in Dry ceiling.
ZEB-R-X Lit Cross-Shaped Configuration Make to Order (Enter side lengths A, B,C and D, ex. X02/02/02/02)*				RH QuickShip Trimless Mount by T-grid hooks to secure in T-grid ceiling / Drop ceiling.
ZEB-R-Y Lit Y-Shaped Configuration Make to Order (Enter side lengths A,B and C, ex. Y04/04/04)*				
ZEB-R-H Lit Hexagon-Shaped Configuration (Enter side lengths A, ex. H04)* Make to Order				
ZEB-R-W Ceiling to Wall Configuration (Enter side lengths A and B, ex. W12/24) QuickShip				



Shape orientation Looking from the Ceiling down to the floor. All corners of shape must be 90° or 120°, same plane. joiners and rolling lens will be included. FOR more complex shape, CONTACT OKT.


ZETA 2.3" Recessed

Spec-grade | Architectural LED Linear Lighting

MOUNTING

Trim **RT**


RT1: Mount by flanged trim and bracket in Dry ceiling.



Mounting Kits



RT2: Mount by flanged trim and pendant stem in Dry ceiling.




Mounting Kits



RT3: Mount by flanged trim to lay on T-grid ceiling/Drop ceiling.



1/4"-20 nut (Supplied by others) 1/4"-20 Threaded rod to structure




Mounting Kits



Trimless

RS

Mount by trimless flanged kit and need plastering in Dry ceiling.






Mounting Kits



RH

Mount by T-grid hooks to secure in T-grid ceiling / Drop ceiling.



Mounting Kits




! Attention: For seamless continuous runs in standard or existing T-grid ceilings, OKT's telescoping section (1"-12") covers the gap between the fixture end and the T-grid.


ZETA 2.3" Recessed

Spec-grade | Architectural LED Linear Lighting


MOUNTING LOCATION




INDIVIDUAL FIXTURE DIMENSION



UNIT DIMENSION FOR SEAMLESS RUNS



JOINER OPTIONS





ZETA 2.3" Recessed

Spec-grade | Architectural LED Linear Lighting


OPTIONAL FUNCTION

► Integral Sensor Options (Diffuser Only)

				
				
				
LUTRON Athena RF Only	LUTRON Athena Sensor			
Keilton				
Lighting Distribution	Function	Sensor Options		
100% Down	Dimming Only		☐ OCC-DDM-A01 QuickShip	A-WN-D01-RF-WH Athena wireless node (RF only) (White)
			☐ OCC-DDM-A02 QuickShip	A-WN-D01-RF-BL Athena wireless node (RF only) (Black)
100% Down	Dimming and Tunable White (3000K-4000K)		☐ OCC-DDM-A03 QuickShip	A-WN-D01-OCC-WH Athena wireless node with sensor (White)
			☐ OCC-DDM-A04 QuickShip	A-WN-D01-OCC-BL Athena wireless node with sensor (Black)
100% Down	Dimming and Tunable White (3000K-4000K)		☐ OCC-DDM-K01 QuickShip	IFS06R.B1 (Remote Control) Fixture Built-in Low Bay Sensor
			☐ OCC-DDM-K02 QuickShip	IFS108.B2 (App)  Integrated Oval 12V Panel Sensor, 0-10V, Daylight Harvesting,PIR, 5.0 BLE
100% Down	Dimming and Tunable White (3000K-4000K)		☐ OCC-DDT-A01* Make to Order	A-WN-D01-RF-WH Athena wireless node (RF only) (White)
			☐ OCC-DDT-A02* Make to Order	A-WN-D01-RF-BL Athena wireless node (RF only) (Black)
100% Down	Dimming and Tunable White (3000K-4000K)		☐ OCC-DDT-A03* Make to Order	A-WN-D01-OCC-WH Athena wireless node with sensor (White)
			☐ OCC-DDT-A04* Make to Order	A-WN-D01-OCC-BL Athena wireless node with sensor (Black)
100% Down	Dimming and Tunable White (3000K-4000K)		☐ OCC-DDT-K01* Make to Order	IFS108.B1 (App)  Integrated Oval 12V Panel Sensor, Dual 0-10V, Daylight Harvesting,PIR, 5.0 BLE
				
For more info or spec sheet please contact sales.				

For more info or spec sheet please contact sales.

► Emergency Options


Location	Wiring Type	Emergency Options	
EMI Built-in EM Only for diffuser, 4ft length	DC Wiring		
EME External Field-installed, works for all options	AC Wiring		
		 ☐ EM-S0854-RBN QuickShip 8W output for 90+ minutes runtime during outages	 2.8"
		 ☐ EM-H16170-RBF QuickShip ☐ EM-H25170-RBF QuickShip 16W or 25W output for 90+ minutes runtime during outages	

For more info or spec sheet please visit <https://www.oktlighting.com/collections/LED-emergency-driver> or contact sales.

ZETA 2.3" Recessed

Spec-grade | Architectural LED Linear Lighting


DISTRIBUTION DIAGRAM



Zonal Flux Diagram					
	C0	C45	C90	C135	C180
10	1418	1421	1412	1398	1411
20	1340	1346	1331	1303	1327
30	1215	1225	1204	1164	1195
40	1049	1064	1038	988.4	1026
50	852.4	870.0	840.6	783.6	826.6
60	629.7	649.8	617.5	555.5	603.1
70	391.9	412.3	377.6	316.3	365.5
80	162.5	178.2	145.8	98.44	139.5
90	2.417	8.146	0.2768	0.4688	0.9405
100	0.5822	0.5917	0.6472	0.7610	0.6802
110	1.012	1.048	1.172	1.246	1.138
120	1.530	1.577	1.753	1.778	1.633
130	2.021	2.104	2.307	2.298	2.124
140	2.524	2.612	2.799	2.780	2.595
150	3.936	3.052	3.178	3.148	3.016
160	3.376	3.422	3.497	3.478	3.442
170	3.769	3.686	3.712	3.724	3.716
180	3.894	3.751	3.759	3.755	3.904
DEG	LUMINOUS INTENSITY:cd				

Zonal Lumens	
	φ total
0-10	136.4
10-20	526.2
20-30	1115
30-40	1822
40-50	2553
50-60	3211
60-70	3708
70-80	3986
80-90	4058
90-100	4059
100-110	4060
110-120	4061
120-130	4063
130-140	4064
140-150	4066
150-160	4068
160-170	4069
170-180	4069
UNIT: lm	

Luminance cd/(m2)		
G(DEG)	C0/180	C90/270
85	10884	8777
80	13119	11617
75	14803	13683
70	16064	15274
65	16980	16310
60	17655	17084
55	18170	17649
50	18591	18090
45	18924	18435



Zonal Flux Diagram					
	C0	C45	C90	C135	C180
10	1583	1593	1552	1494	1546
20	1434	1513	1475	1304	1347
30	1163	1339	1349	1044	1044
40	790.0	1073	1178	714.1	652.8
50	382.2	734.4	972.0	357.8	253.6
60	60.93	354.3	733.4	66.49	9.481
70	3.607	50.38	472.8	3.429	1.964
80	1.129	3.391	209.4	1.111	0.5673
90	0.2172	0.8545	0.4901	0.1488	0.1127
100	0.1263	0.1488	0.6813	0.2888	0.1309
110	0.1532	0.3044	1.232	0.7484	0.2482
120	0.4461	0.7326	1.867	1.429	0.6274
130	1.000	1.326	2.485	2.185	1.259
140	1.740	2.047	2.990	2.888	2.048
150	2.579	2.800	3.400	3.436	2.864
160	3.454	3.432	3.725	3.853	3.604
170	4.080	3.887	3.937	4.115	4.176
180	4.329	4.088	3.973	4.031	4.324
DEG	LUMINOUS INTENSITY:cd				


Zonal Lumens	
	φ total
0-10	150.3
10-20	574.1
20-30	1189
30-40	1871
40-50	2474
50-60	2884
60-70	3092
70-80	3165
80-90	3176
90-100	3176
100-110	3177
110-120	3178
120-130	3179
130-140	3180
140-150	3182
150-160	3184
160-170	3185
170-180	3185
UNIT: lm	

Luminance cd/(m2)		
G(DEG)	C0/180	C90/270
85	91	14627
80	90	16749
75	110	18232
70	146	19198
65	212	19878
60	1692	20373
55	4751	20732
50	8259	21002
45	11457	21208

ZETA 2.3" Recessed

Spec-grade | Architectural LED Linear Lighting


DISTRIBUTION DIAGRAM



Zonal Flux Diagram					
	C0	C45	C90	C135	C180
10	645.7	610.0	572.8	575.5	641.7
20	587.1	526.2	462.3	462.7	577.7
30	486.9	413.4	331.5	334.2	473.3
40	351.7	286.0	191.4	205.6	336.2
50	205.1	164.5	118.0	108.3	190.8
60	90.14	93.22	76.60	62.48	83.96
70	48.20	54.13	44.63	31.41	45.20
80	18.14	24.87	19.03	7.752	16.38
90	0.0943	2.294	0.0883	0.0823	0.0696
100	0.0964	0.1004	0.0997	0.1329	0.1092
110	0.1738	0.1566	0.1725	0.2238	0.1899
120	0.3161	0.2657	0.2690	0.3677	0.3403
130	0.5296	0.4396	0.4225	0.5662	0.5586
140	0.7842	0.6746	0.6471	0.8129	0.8181
150	1.061	0.9656	0.9161	1.073	1.087
160	1.341	1.250	1.209	1.318	1.338
170	1.532	1.462	1.427	1.492	1.541
180	1.601	1.541	1.498	1.507	1.609
DEG	LUMINOUS INTENSITY:cd				

Zonal Lumens	
	φ total
0-10	59.69
10-20	217.7
20-30	427.4
30-40	632.8
40-50	788.8
50-60	891.2
60-70	954.3
70-80	987.8
80-90	997.0
90-100	997.3
100-110	997.4
110-120	997.7
120-130	998.0
130-140	998.4
140-150	999.0
150-160	999.5
160-170	999.9
170-180	1000
UNIT: lm	

Luminance cd/(m2)		
G(DEG)	C0/180	C90/270
85	3109	3709
80	4137	4340
75	4858	4760
70	5581	5167
65	6368	5591
60	7139	6066
55	9642	6635
50	12635	7267
45	15571	7976



Zonal Flux Diagram					
	C0	C45	C90	C135	C180
10	5120	5391	6262	6029	6239
20	4896	5241	4784	3135	5119
30	1657	2590	1455	264.5	1580
40	9.002	56.68	19.20	2.505	4.747
50	1.409	2.120	1.266	1.071	1.356
60	0.4646	0.7645	0.3787	0.3856	0.3831
70	0.3384	0.3652	0.3562	0.2976	0.2838
80	0.2346	0.3111	0.3337	0.2684	0.1577
90	0.1624	0.2953	0.2734	0.1060	0.0992
100	0.1218	0.1060	0.0812	0.1330	0.1264
110	0.1353	0.1128	0.1082	0.1330	0.1264
120	0.1443	0.1466	0.1443	0.1961	0.1578
130	0.2927	0.2661	0.4698	0.9288	0.3029
140	1.738	1.413	2.014	3.406	1.947
150	5.366	4.428	5.017	6.687	5.339
160	9.258	7.999	8.278	10.02	8.626
170	12.95	11.55	11.38	12.86	12.68
180	14.54	13.72	12.85	12.94	14.57
DEG	LUMINOUS INTENSITY:cd				

Zonal Lumens	
	φ total
0-10	540.7
10-20	2029
20-30	3479
30-40	3822
40-50	3828
50-60	3829
60-70	3829
70-80	3830
80-90	3830
90-100	3830
100-110	3830
110-120	3830
120-130	3831
130-140	3831
140-150	3834
150-160	3837
160-170	3840
170-180	3841
UNIT: lm	


Luminance cd/(m2)		
G(DEG)	C0/180	C90/270
85	31	47
80	19	27
75	15	19
70	14	14
65	13	12
60	13	11
55	18	15
50	30	27
45	43	52

ZETA 2.3" Recessed

Spec-grade | Architectural LED Linear Lighting


DISTRIBUTION DIAGRAM

4' / Diffuser Wall Wash / 4000K



Lumens: 4602.1 Lm
Watts: 41.95 W
LPW: 109.71 Lm/W
CCT: 4000K

UNIT: cd
— C0/180, 81.4°
— C30/270, 85°
— C60/240, 95.3°
— C90/270, 103.8°



Zonal Flux Diagram

	C0	C45	C90	C135	C180
10	2010	1892	1670	1472	1483
20	2106	1945	1568	1184	1126
30	2066	1891	1398	927.9	861.6
40	1860	1716	1174	715.0	661.5
50	1489	1408	904.0	528.6	494.0
60	1086	996.3	622.2	361.1	345.2
70	553.6	571.0	356.6	210.1	208.9
80	213.5	226.9	137.6	82.39	92.18
90	14.38	17.50	1.568	1.378	4.851
100	5.281	2.620	0.6399	0.9592	0.9344
110	1.389	0.8569	1.168	1.720	1.700
120	1.055	1.211	1.816	2.574	2.615
130	1.424	1.613	2.405	3.370	3.507
140	1.853	2.077	2.993	3.994	4.244
150	2.385	2.631	3.488	4.418	4.753
160	3.118	3.275	3.898	4.626	5.061
170	4.023	3.919	4.192	4.626	5.093
180	4.706	4.381	4.215	4.300	4.720
DEG	LUMINOUS INTENSITY:cd				

Zonal Lumens

	φ total
0-10	163.5
10-20	625.8
20-30	1318
30-40	2145
40-50	2988
50-60	3717
60-70	4233
70-80	4509
80-90	4586
90-100	4590
100-110	4591
110-120	4593
120-130	4595
130-140	4597
140-150	4599
150-160	4061
160-170	4062
170-180	4062
UNIT	lm

Luminance cd/(m2)

G(DEG)	C0/180	C90/270
85	14792	9050
80	17074	11003
75	19709	12753
70	22480	14479
65	25273	15947
60	28006	17283
55	30421	18643
50	32173	19532
45	33247	20509