

Catalog Number : _____ Project Name: _____ Note : _____ Date : _____ Type: _____


DESCRIPTION

Ultra slim design, lamp thickness only 0.39".

Features color tunable technology lets the user choose between 2700K,3000K, 3500K, 4000K,or 5000K.

IC rated for direct contact with insulation.Wet-location rated, ideal for bathrooms, laundry rooms and garage work rooms.

Available size: 4",6".



4" / 6"



BASED ON SAMPLE SETTING. ACTUAL LUMENS MAY VARY.

MODEL#	SIZE	WATTAGE	5CCT	LUMENS
DM-4EJCT09SR05	4inch	9W	2700K	562Lm
			3000K	613Lm
			3500K	637Lm
			4000K	644Lm
			5000K	602Lm

MODEL#	SIZE	WATTAGE	5CCT	LUMENS
DM-6EJCT12SR05	6inch	12W	2700K	936Lm
			3000K	996Lm
			3500K	1038Lm
			4000K	1041Lm
			5000K	998Lm



TECHNICAL SPECIFICATION.

VOLTAGE	120V
POWER FREQUENCY	60Hz
POWER FACTOR	>0.9
5CCT	2700K 3000K 3500K 4000K 5000K
CRI	80
BEAM ANGLE	120°

MATERIAL	PS+AL
LIFESPAN	≥50,000hours
OPERATING TEMP	(-4° F~ 113° F) -20~45° C
DIMMABLE	Triac Dimming
RATING	Suitable for Wet Locations
WARRANTY	5 year limited

INSTALLATION

No existing recessed housing or junction box required.

Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10%dimming to choose the desired brightness.

Please check the recommended dimmer list in next page.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

ETL Listed. Energy Star. Title24.



Catalog Number : _____ Project Name: _____ Note : _____ Date : _____ Type: _____

Easily flip the switch for desired CCT



SIZE & DIMENSION & HOLE SIZE

SIZE	DIMENSION	HOLE SIZE
4inch		 $\Phi 4 \frac{21}{64}''$ (110mm)
6inch		 $\Phi 6 \frac{19}{64}''$ (160mm)

RECOMMENDED DIMMER

LUTRON			LEVITON		
TG-600PR-WH	TGCL-153PH-LA	SCL-153PH-WH	PD-6WCL	6672	
S-600PR-WH	SLV-600P-AL	GT-600P	MACL-153M//MA-R	6674	RNL06
CTCL-153PDH-WH	DV-600PR-WH	DVCL-153P	MSCL-OP153M	DSL06	IPL06

TRIM RING REPLACEMENT (SOLD SEPARATELY)	ACCESSORIES		
 Brushed nickel Black Bronze	 J-Box driver	 Connector	 Hole cutout card