Installation Introduction



According to the cut size to cut the ceiling hole.



Cut off power,the driver wire connected with ceiling wire.





Insert panel light into the ceiling hole





Install finishing

- Input voltage AC100-130V,Please power off when installation to prevent electric shock.
- Product Ip20 waterproof level,Indoor use only and don't used in high temperature place
- Please note,this fixture must be wired in accordance with Local electrical codes and ordinances.ALL work must be done By a certified electrician.
- Risk of electric shock,do not use where directly exposed to water and make sure power is OFF from electrical.

Round hole size

N0.	voltage	size	cut size	power	lumen	LED
1	AC100-130V	120x120mm	105x105mm	9w	650lm	SMD2835
2	AC100-130V	175x175mm	160x160mm	12w	1000lm	SMD2835
3	AC100-130V	225x225mm	210x210mm	18w	1800lm	SMD2835

INSTALLATION GUIDE

INSTALLATION GUIDE

THANK YOU for buying this product. To help ensure it gives complete satisfaction please install it according to these instructions and then pass the instructions to the appropriate person for retention and future reference.

IMPORTANT SAFETY INFORMATION

(1) Please turn off the power before cleaning the light fitting, and use dry and soft fabric, don't use chemical or corrosive things.
(2)Ensure the product is intact before installing.
(3)Avoid looking at the LED light-emitting area directly.
(4)Non-professional person is prohibited dismantling and repairing, we won't provide the replacing or repairing service for products which have been privately dismantled and repaired.
(5) The distance between the products and inflammable material should at least be 0.2m.
(6) Ensure the wire of power supply is long enough, avoid big tension, don't tie a knot,don't mix up the output wire.
(7) Don't use the professional LED panel driver for other lighting.

